

Safety & Area Marking Tape



ToughStripe® Floor Marking Tape Roll

- » Visible floor-marking improves safety and organization in almost any industrial environment
- » High-gloss surface shines like new paint and withstands forklift traffic without tearing or lifting
- » Ideal for marking aisles, passageways and storage locations and identifying equipment and egress paths

ITEM #	ORDER #	DESCRIPTION	UOM
2" x 100'			
104311	J05200581	White	RL
104312	J05200531	Yellow	RL
104313	J05200511	Red	RL
104314	J05200461	Blue	RL
104315	J05200641	Green	RL
104316	J05200541	Orange	RL
104317	J05200561	Black/Yellow Strip	RL
3" x 100'			
104342	J05200491	Yellow	RL
104347	J05200631	Black/Yellow Strip	RL
4" x 100'			
104372	J05200601	Yellow	RL
104377	J05200651	Black/Yellow Strip	RL



91420



91423



Pipe Marking Directional Flow Arrow Tape Vinyl


- » High gloss, durable, flexible vinyl with a permanent cold temperature pressure sensitive acrylic adhesive
- » Good chemical, oil and water resistance
- » Item comes in end-user packaging for use in point-of-purchase displays
- » Supplied in liner-mounted rolled form - use two bands per pipe marker

ITEM #	ORDER #	DESCRIPTION	UOM
2" x 30 yd			
91420	J05201081	Yellow/Black Arrows	RL
91421	J05201091	Green/White Arrows	RL
91423	J05201101	Blue/White Arrows	RL
1" x 30 yd			
91424	J05201111	Yellow/Black Arrows	RL
91425	J05201121	Green/White Arrows	RL



ToughStripe® Floor Corner L-Shaped Marking Tape, Yellow

- » Visible floor-marking improves safety and organization in almost any industrial environment
- » High-gloss surface shines like new paint and withstands forklift traffic without tearing or lifting
- » Ideal for marking corners of work cells and storage locations
- » Can be easily applied by one person
- » 2" wide x 5" long



104433

ITEM #	ORDER #	DESCRIPTION	UOM
104433	J05201005	Corner L-Shaped Marking Tape	20/Pk



Masking Tape

3M



70006745700

3M™ High Performance Green Masking Tape 401+

- » Removes cleanly in one piece with no adhesive residue
- » Remains in place around corners, over contours and irregular surfaces
- » Resists paint bleed-through to help create sharp paint lines
- » Green backing improves visibility and accuracy during paint masking
- » Withstands surface temperatures up to 250°F/121°C for 30 minutes in paint bake operations

ITEM #	ORDER #	DESCRIPTION	UOM
70006745700	66552726	24 mm x 55 m, 6.7 mil Thick	24/Cs
70006745718	66552727	36 mm x 55 m, 6.7 mil Thick	16/Cs
70006745726	66552728	48 mm x 55 m, 6.7 mil Thick	12/Cs
70006745734	665527291	72 mm x 55 m, 6.7 mil Thick	8/Cs

3M

3M™ High Performance Yellow Masking Tape 301+

- » Proprietary, solvent-free adhesive formula removes cleanly in one-piece with no adhesive residue
- » Withstands surface temperatures up to 225°F/107°C for 30 minutes
- » Resists paint bleed-through to help create good paint lines
- » Sticks with confidence on rubber moldings, plastic, glass, wood, concrete, metal and painted surfaces
- » Yellow backing improves visibility and accuracy during paint masking
- » Remains in place around corners, over contours and irregular surfaces



70006745635

ITEM #	ORDER #	DESCRIPTION	UOM
70006745635	66554199	72 mm x 55 m, 6.3 mil Thick	12/Cs

3M

3M™ General Purpose Tan Masking Tape 231/231A

- » Rubber adhesive provides strong tack and adhesion and resists lifting
- » Clean removal from many surfaces following multi-bake or high temperature bake
- » Smooth mini-crepe paper backing conforms and maintains integrity when formed around a corner
- » Strong backing is easy to tear, yet resists slivering and provides one-piece removal
- » Controlled unwind dispenses evenly, reducing fatigue



GT500030199

ITEM #	ORDER #	DESCRIPTION	UOM
GT500030199	66552491	24 mm x 55 m, 7.6 mil Thick	36/Cs
GT500030215	66554200	48 mm x 55 m, 7.6 mil Thick	24/Cs

3M

3M™ General Purpose Tan Masking Tape 234

- » Strong backing is easy to tear, yet resists slivering and provides one-piece removal
- » Rubber adhesive provides instant adhesion and resists lifting or curling, yet still removes easily
- » Crepe paper backing conforms and maintains integrity when formed around a corner
- » Performs well in paint bake operations up to 250°F for 30 minutes
- » Manufactured without solvents for reduced environmental impact

ITEM #	ORDER #	DESCRIPTION	UOM
70006319290	665542021	24 mm x 55 m, 5.9 mil Thick	RL
70006319308	665531101	48 mm x 55 m, 5.9 mil Thick	RL



70006319290

Masking Tape

3M

Scotch® Green Fine Line Tape 218

- » High-performance polypropylene plastic tape
- » Thin tape provides excellent color line separation
- » Proven excellent for painting long straight lines and smooth curves
- » Resistant to most solvents and moisture
- » Resists heat in bake cycles that reach 250°F/121°C for up to 30 minutes



70006028693

ITEM #	ORDER #	DESCRIPTION	UOM
70006028693	665537881	2" x 60 yd., 5.0 mil Thick	RL



GT500015844

3M

3M™ Performance Tan Masking Tape 2380

- » Provides strong holding power and exceptional high-temperature resistance
- » Resists slivering when exposed to high heat
- » Removes cleanly after 30 minutes at bake temperatures up to 325°F/162°C
- » Heavy crepe paper backing resists bleed-through
- » Adhesive bonds instantly to many surfaces, holding in place without lifting or curling
- » Strong backing is easy to tear and provides one-piece removal

ITEM #	ORDER #	DESCRIPTION	UOM
GT500015844	665538701	48 mm x 55 m, 7.3 mil Thick	RL

3M

3M™ Tan Masking Tape 2307


- » General purpose tape for woodworking
- » Rubber adhesive offers broad tack and moderate adhesion
- » Crepe-paper backing conforms over irregular surfaces, contours and around corners

ITEM #	ORDER #	DESCRIPTION	UOM
70006159522	66553264	24 mm x 55 m, 5.2 mil Thick	36/Cs



70006159522

Duct Tape



3M

3M™ Performance Plus Slate Blue Duct Tape 8979

- » Removes cleanly for up to six months from most opaque surfaces even after UV exposure to sun and outdoor weathering
- » Sticks immediately and stays on for up to one-year without deterioration
- » Strong water-resistant backing resists wear and light abrasion
- » Provides a tight, moisture-resistant seal in many containment situations
- » Conforms to irregular surfaces without lifting

ITEM #	ORDER #	DESCRIPTION	UOM
70006413457	665542051	48 mm x 54.8 m, 12.1 mil Thick	RL
70006413465	665542041	72 mm x 54.8 m, 12.1 mil Thick	RL

Duct Tape



3M™ Silver Duct Tape

- » For use in MRO/construction applications
- » Removes cleanly for up to three months when applied indoors
- » Sticks immediately and stays on for up to one-year without deterioration
- » Water-resistant backing resists wear and light abrasion
- » Provides a tight, moisture-resistant seal in many containment situations
- » Conforms to irregular surfaces without lifting



70006720661



70006250602



70006250172

ITEM #	ORDER #	DESCRIPTION	UOM
48 mm x 54.8 m, (1.88" x 60 yd.)			
70006720661	665542311	Value 1900, 5.8 mil Thick	RL
70006250602	665508291	Multi-Purpose 3900, 7.7 mil Thick	RL
70006250172	665516461	Extra Heavy-Duty 6969, 10.7 mil Thick	RL



70006413572



3M™ Performance Plus Duct Tape 8979N

- » Resists UV, sunlight and weather to stay on for up to one-year without deterioration
- » Distinctive red and slate blue color available
- » Complies with MIL-STD-2041D(SH), Notice 2 for leachable halides and sulfur
- » Curl-resistant, moisture-resistant and conformable backing for easy handling
- » Removes cleanly from most opaque surfaces after up to six months of UV exposure and weather



70006356003

ITEM #	ORDER #	DESCRIPTION	UOM
Slate Blue			
70006413564	66554208	48 mm x 54.8 m, 12.1 mil Thick	24/Cs
70006413572	66554214	72 mm x 54.8 m, 12.1 mil Thick	12/Cs
Nuclear Red			
70006355997	66554215	48 mm x 54.8 m, 12.1 mil Thick	24/Cs
70006356003	66554216	72 mm x 54.8 m, 12.1 mil Thick	12/Cs



70005025054



3M™ Poly & Tarps Gray Duct Tape

- » High adhesion to heavy-weight poly
- » High tensile strength that resists tearing
- » Great for repairing tarps and securing drop cloths
- » Water resistant and temperature flexible
- » Conformable for a tight, long-lasting seal
- » UL 723 compliant

ITEM #	ORDER #	DESCRIPTION	UOM
70005025054	66552977	48 mm x 54.8 m, (1.88" x 60 yd.)	9/Cs



3M™ Vinyl Yellow Duct Tape 3903

- » Rubber adhesive sticks fast and stays fast on many surfaces, even irregular surfaces
- » Embossed vinyl backing seals out dust, dirt and moisture and resists abrasion and many chemicals
- » Peels off cleanly after 30 minutes on painted steel as hot as 200°F (93°C)
- » Easy to tear and conforms to irregular surfaces



70007507034

ITEM #	ORDER #	DESCRIPTION	UOM
70007507034	66553983	2" x 50 yd., 6.5 mil Thick	24/Cs

Electrical Tape



80610833867

WARNING: Cancer - www.P65Warnings.ca.gov



Scotch® Professional Grade Vinyl Electrical Tape Super 88

- » The combination of the pressure-sensitive, rubber-resin adhesive and the PVC backing offers excellent electrical and mechanical protection
- » Provides high resistance to UV rays, abrasion, moisture, alkalis, acids and corrosion
- » Withstands a temperature range of 0° to 221°F (-18° to 105°C)
- » Provides a protective jacket and electrical insulation for splices and cables
- » Tensile strength rating of 20 lbs. per inch
- » UL Listed, CSA Certified and RoHS 2011/65/EU Compliant

ITEM #	ORDER #	DESCRIPTION	UOM
80610833867	665525431	Black PVC, 0.75" x 66 ft., 8.5 mil Thick	RL



Scotch® Super 33+™ Vinyl Electrical Tape

- » The combination of the pressure-sensitive, rubber-resin adhesive and the PVC backing offers excellent electrical and mechanical protection
- » Provides high resistance to UV rays, abrasion, moisture, alkalis, acids and corrosion
- » Withstands a temperature range of 0° to 221°F (-18° to 105°C)
- » Compatible with rubber and synthetic splicing compounds
- » Tensile strength rating of 15 lbs. per inch
- » UL Listed, CSA Certified and RoHS 2011/65/EU Compliant

WARNING: Cancer - www.P65Warnings.ca.gov



80610833834

ITEM #	ORDER #	DESCRIPTION	UOM
80610833834	665515681	Black PVC, 0.75" x 66 ft., 7 mil Thick	RL



Scotch® Vinyl Color Coding Red Electrical Tape 35

- » Electrical and mechanical protection from combined pressure-sensitive, rubber-resin adhesive and PVC backing
- » Suitable for use in phase identification, color coding of motor leads and piping systems and for marking safety areas
- » Withstands a temperature range of 32° to 221°F (0° to 105°C)
- » Tensile strength rating of 17 lbs. per inch
- » UL Listed, CSA Certified and RoHS 2011/65/EU Compliant

WARNING: Cancer - www.P65Warnings.ca.gov



80610833909

ITEM #	ORDER #	DESCRIPTION	UOM
80610833909	665539091	Red PVC, 0.75" x 66 ft., 7 mil Thick	RL

Painter's Tape



ScotchBlue™ Original Painter's Tape 2090

- » Ideal for use on smooth or lightly textured walls, trim, glass and metal
- » Sharp paint lines on a variety of surfaces
- » Removes cleanly up to 14 days with no sticky residue
- » Medium adhesion level removes easily, while protecting your surfaces
- » Indoor or outdoor use



70006960200

ITEM #	ORDER #	DESCRIPTION	UOM
70006960200	665537855	48 mm x 54.8 m, (1.88" x 60 yd.), 5.4 mil Thick	6/Pk
70006576543	665530651	48 mm x 54.8 m, (1.88" x 60 yd.), 5.4 mil Thick	RL



Specialty Tape



70006658192

3M

3M™ High Performance Double Coated Tape 9086

- » Double coated tape with tissue carrier, acrylic adhesive
- » High tack, immediate bond, quick stick, high adhesion and good initial adhesion
- » Solvent resistant
- » Bonds to a wide variety of materials and substrates

ITEM #	ORDER #	DESCRIPTION	UOM
70006658192	665530721	White, 1" x 55 yd., 7.5 mil Thick	RL



70006006301

3M

3M™ Adhesive Transfer Tape Extended Liner

- » Pressure sensitive adhesives
- » Dry edge and finger lift edge liners
- » Tack free tape roll edges for ease of use
- » Easy liner starting and removal

ITEM #	ORDER #	DESCRIPTION	UOM
70006006301	66554163	Translucent, 0.75" x 1000 yd., 1.0 mil Thick	9/Cs



7000028907

3M

Scotch® Box Sealing Tape 375

- » High edge tear and split resistance
- » Polypropylene backing with synthetic rubber adhesive
- » Easy unwind and smooth dispensing
- » Resists abrasion, moisture, chemicals and scuffing
- » Excellent adhesion to recycled liner paper and fiberboard

ITEM #	ORDER #	DESCRIPTION	UOM
7000028907	665537511	Clear, 48 mm x 50 m, 3.1 mil Thick	RL
70006182920	665538611	Tan, 48 mm x 50 m, 3.1 mil Thick	RL



70006295037

3M

3M™ Impact Stripping Tape 528

- » Tan, durable backing protects against a variety of blasting media
- » Acrylic adhesive provides reliable bond
- » Adhesive helps ensure clean, one-piece removal without residue
- » Easy release paper liner makes for efficient die-cutting

ITEM #	ORDER #	DESCRIPTION	UOM
70006295037	665538461	Tan, 4" x 20 yd., 85.0 mil Thick	RL

3M

3M™ Preservation Sealing Tape 481

- » Effective for many outdoor applications with quick, clean removal when finished
- » Helps preserve equipment and vehicles for long-term storage of at least two years
- » Can be certified to Military Specification: SAE AMS-T-22085
- » Resistance to staining, common lubricants and strippable coatings on a variety of surfaces
- » Polyethylene backing

ITEM #	ORDER #	DESCRIPTION	UOM
70006021078	665538621	Black, 2" x 36 yd., 9.5 mil Thick	RL



70006021078

Specialty Tape

3M

3M™ All Weather Flashing Tape 8067

- » Apply at surface temperatures as low as 0°F (-18°C) or high as 176°F (80°C)
- » Resists UV exposure for up to 12 months
- » Passes nail sealability before and after thermal cycling according to AAMA 711-05
- » Bonds to most common building materials without primers and staples
- » Service temperature -40° to 240°F (-40° to 116°C)
- » No adverse reaction with many building sealants
- » Split-liner for easy and accurate positioning of tape, especially long lengths



70006745015

ITEM #	ORDER #	DESCRIPTION	UOM
70006745015	665539881	Tan, 4" x 75 ft., Slit Liner	RL

Spray Adhesives



62497749309

3M

3M™ Super 77™ Multipurpose Spray Adhesive

- » Provides professional, industrial strength for demanding applications
- » Bonds paper, cardboard, fabric, insulation, plastic, metal, wood and more
- » Allows for a bond time of 15 seconds to 30 minutes
- » Repositionable while providing long-lasting strength

ITEM #	ORDER #	DESCRIPTION	UOM
62497749309	66550012	Aerosol, 24 Fluid Oz., Net. Wt. 16.75 oz.	12/Cs

3M

3M™ Foam Fast 74 Spray Adhesive

- » Designed specifically for foams and fabrics
- » Dispenses with a lace-spray pattern optimized for foam bonding
- » Provides professional, industrial strength for demanding applications
- » Offers a fast, aggressive tack for a quick assembly of high-stress bonds
- » Allows for a bond time of 15 seconds to 30 minutes

ITEM #	ORDER #	DESCRIPTION	UOM
62493549505	66553866	Orange Aerosol, 24 Fluid Oz., Net. Wt. 16.9 oz.	12/Cs
62495049504	66554225	Clear Aerosol, 24 Fluid Oz., Net. Wt. 16.9 oz.	12/Cs



62493549505



62493349500

3M

3M™ Pressure Sensitive Spray Adhesive 72

- » Pressure sensitive adhesive gains strength as pressure is applied
- » Permanent tack ideal for many one-surface bond applications
- » Low soak-in formula keeps adhesive on the surface
- » Long open time allows bonds to be made hours or days after application
- » Variable width lace spray pattern allows for precise dispensing

ITEM #	ORDER #	DESCRIPTION	UOM
62493349500	66554224	Aerosol, 24 Fluid Oz., Net. Wt. 17.3 oz.	12/Cs