

MSA V-TEC® Mini Personal Fall Limiter



Material Specifications

WEIGHT	See tables
RETRACTED LENGTH	See tables
TOTAL UNIT LENGTH 6 ft. (1.8 m)	72 in. (1.8m)
UNIT WIDTH SINGLE-LEG PFL TWIN-LEG PFL	3 in. (76.2 mm) 6 in. (152.4 mm)
HOUSING DEPTH 6 ft. (1.8 m) PFL	2.23 in. (56.64 mm)
HOUSING MATERIAL	Polycarbonate
HARDWARE MATERIALS	Steel or Aluminum
LIFELINE MATERIAL	2/3 in. (17 mm) wide / 0.06 in. (1.4 mm) thick HMPE
ENERGY ABSORBING TECHNOLOGY	47 in. (1200 mm.) Tear Tape



Ordering Information

V-TEC Web PFL - ANSI					
Part Number	Single/Twin	Top Hook	Lifeline Hook	Retracted Length	Weight
VTOHW-011-DA-A	Single	ALTAK	AL36CL	28.36 in. (720.3 mm)	3.15 lb. (1.42 kg)
VTOHW-011-DB-A	Single	ALTAK	36C	24.4 in. (619.8 mm)	2.65 lb. (1.20 kg)
VTOHW-011-DC-A	Single	ALTAK	ALTAKS	25.68 in. (652.3 mm)	2.25 lb. (1.02 kg)
VTOHW-011-DD-A	Single	ALTAK	ALTAK	23.4 in. (594.4 mm)	2.07 lb. (0.94 kg)
VTOHW-011-DE-A	Single	ALTAK	36CS	25.48 in. (647.2 mm)	2.89 lb. (1.31 kg)
VTOHW-011-DF-A	Single	ALTAK	36CL	28.2 in. (716.3 mm)	3.59 lb. (1.63 kg)
VTOHW-011-ZA-A	Single	NONE	AL36CL	23.47 in. (596.1 mm)	2.87 lb. (1.30 kg)
VTOHW-011-ZB-A	Single	NONE	36C	19.51 in. (495.6 mm)	2.36 lb. (1.07 kg)
VTOHW-011-ZC-A	Single	NONE	ALTAKS	20.8 in. (528.3 mm)	1.94 lb. (0.88 kg)
VTOHW-011-ZD-A	Single	NONE	ALTAK	18.51 in. (470.2 mm)	1.79 lb. (0.81 kg)
VTOHW-011-ZE-A	Single	NONE	36CS	20.6 in. (523.2 mm)	2.6 lb. (1.18 kg)
VTOHW-011-ZF-A	Single	NONE	36CL	23.32 in. (592.3 mm)	3.31 lb. (1.50 kg)
VTOHW-012-RA-A	Twin	TLALTAK	AL36CL	26.43 in. (671.3 mm)	6.08 lb. (2.76 kg)
VTOHW-012-RB-A	Twin	TLALTAK	36C	22.47 in. (570.7 mm)	5.07 lb. (2.30 kg)
VTOHW-012-RC-A	Twin	TLALTAK	ALTAKS	23.75 in. (603.3 mm)	4.25 lb. (1.93 kg)
VTOHW-012-RD-A	Twin	TLALTAK	ALTAK	21.47 in. (545.3 mm)	3.9 lb. (1.77 kg)
VTOHW-012-RE-A	Twin	TLALTAK	36CS	23.55 in. (598.2 mm)	5.56 lb. (2.52 kg)
VTOHW-012-RF-A	Twin	TLALTAK	36CL	26.27 in. (667.3 mm)	6.97 lb. (3.16 kg)
VTOHW-011-DJ-O-TB	Single	ALTAK	FP5K	59.61 in. (1514.1 mm)	2.71 lb. (1.23 kg)
VTOHW-012-RJ-O-TB	Twin	TLALTAK	FP5K	57.68 in. (1462.0 mm)	5.18 lb. (2.35 kg)

WE KNOW WHAT'S AT STAKE.

Ordering Information

V-TEC Web PFL - CSA					
Part Number	Single/Twin	Top Hook	Lifeline Hook	Retracted Length	Weight
VTOHW-011-DA-C	Single	ALTAK	AL36CL	28.36 in. (720.34 mm)	3.15 lb. (1.43 kg)
VTOHW-011-DB-C	Single	ALTAK	36C	24.4 in. (619.76 mm)	2.65 lb. (1.2 kg)
VTOHW-011-DC-C	Single	ALTAK	ALTAKS	25.68 in. (652.27 mm)	2.25 lb. (1.02 kg)
VTOHW-011-DD-C	Single	ALTAK	ALTAK	23.4 in. (594.36 mm)	2.07 lb. (0.94 kg)
VTOHW-011-DE-C	Single	ALTAK	36CS	25.48 in. (647.19 mm)	2.89 lb. (1.31 kg)
VTOHW-011-DM-C	Single	ALTAK	36CLS	28.47 in. (723.14 mm)	3.2 lb. (1.45 kg)
VTOHW-011-ZA-C	Single	NONE	AL36CL	23.47 in. (596.14 mm)	2.87 lb. (1.3 kg)
VTOHW-011-ZB-C	Single	NONE	36C	19.51 in. (495.55 mm)	2.36 lb. (1.07 kg)
VTOHW-011-ZC-C	Single	NONE	ALTAKS	20.8 in. (528.32 mm)	1.94 lb. (0.88 kg)
VTOHW-011-ZD-C	Single	NONE	ALTAK	18.51 in. (470.15 mm)	1.79 lb. (0.81 kg)
VTOHW-011-ZE-C	Single	NONE	36CS	20.6 in. (523.24 mm)	2.6 lb. (1.18 kg)
VTOHW-011-ZM-C	Single	NONE	36CLS	23.59 in. (599.19 mm)	2.91 lb. (1.32 kg)
VTOHW-012-RA-C	Twin	TLALTAK	AL36CL	26.43 in. (671.32 mm)	6.08 lb. (2.76 kg)
VTOHW-012-RB-C	Twin	TLALTAK	36C	22.47 in. (570.74 mm)	5.07 lb. (2.3 kg)
VTOHW-012-RC-C	Twin	TLALTAK	ALTAKS	23.75 in. (603.25 mm)	4.25 lb. (1.93 kg)
VTOHW-012-RD-C	Twin	TLALTAK	ALTAK	21.47 in. (545.34 mm)	3.9 lb. (1.77 kg)
VTOHW-012-RE-C	Twin	TLALTAK	36CS	23.55 in. (598.17 mm)	5.56 lb. (2.52 kg)
VTOHW-012-RM-C	Twin	TLALTAK	36CLS	26.55 in. (647.37 mm)	6.17 lb. (2.8 kg)

Available Connectors

V-TEC Mini PFL offers an aluminum top carabiner and a variety of available connectors.

AL36CL	36C	ALTAKS Aluminum Triple Action Carabiner, Non-Indicator Swivel	ALTAK Aluminum Triple Action Carabiner	
36CS Non-Indicator Swivel	36CL	FP5K Tie-back only	36CLS	TLALTAK Twin-Link Aluminum Triple Action Carabiner

Note: This Bulletin contains only a general description of the products shown. While product uses and performance capabilities are generally described, the products shall not, under any circumstances, be used by untrained or unqualified individuals. The products shall not be used until the product instructions/user manual, which contains detailed information concerning the proper use and care of the products, including any warnings or cautions, have been thoroughly read and understood. Specifications are subject to change without prior notice. MSA is a registered trademark of MSA Technology, LLC in the US, Europe, and other Countries. For all other trademarks visit <https://us.msasafety.com/Trademarks>.