

# V-Series Energy-Absorbing Lanyards **Conversion Guide**



CSA

## Complex Worksites. Simplified Solutions.

Our new line of V-Series Lanyards simplifies product selection by offering a concise line of standard lanyards that will meet a wide range of customer needs. All new lanyards shown below also meet the latest CSA standards for lanyards: CSA Z259.11-17.

Old P/N	Description	New CSA P/N	New CSA Lightweight Worker P/N	Description	Standard	
Legacy Lanyards		V-Series Lanyards				
10023932	Diamond Single-Leg Energy-Absorbing Lanyard, 6', 36C steel snaphooks	10188100	10190397	V-Series standard single-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36C small snaphooks	CSA Z259.11-17	
10045936	Diamond Single-Leg Energy-Absorbing Expanyard, 6', 36C steel snaphooks	10188100	10190397	V-Series standard single-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36C small snaphooks	CSA Z259.11-17	
10023936	Diamond Single-Leg Energy-Absorbing Lanyard, 5', 36C steel snaphooks	10188100	10190397	V-Series standard single-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36C small snaphooks	CSA Z259.11-17	
10156529	Diamond LITE Single-Leg Energy-Absorbing Lanyard, 6', AL36C aluminum snaphook	10188100	10190397	V-Series standard single-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36C small snaphooks	CSA Z259.11-17	
10023970	Diamond Twin-Leg Energy-Absorbing Lanyard, 6', 36CS swivel snaphook & (2) 36C steel snaphooks	10188102	10190399	V-Series standard twin-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36C small snaphooks	CSA Z259.11-17	
10023937	Diamond Twin-Leg Energy-Absorbing Lanyard, 5', 36CS swivel snaphook & (2) 36C steel snaphooks	10188102	10190399	V-Series standard twin-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36C small snaphooks	CSA Z259.11-17	
10055189	Diamond Twin-Leg Energy-Absorbing Lanyard 6' 36CS Steel Snaphook	10188102	10190399	V-Series standard twin-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36C small snaphooks	CSA Z259.11-17	
10156530	Diamond LITE Twin-Leg Energy-Absorbing Lanyard, 6', (2) AL36C aluminum snaphook	10188102	10190399	V-Series standard twin-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36C small snaphooks	CSA Z259.11-17	



**WE KNOW WHAT'S AT STAKE.**

Old P/N	Description	New CSA P/N	New CSA Lightweight Worker P/N	Description	Standard
<b>Legacy Lanyards</b>		<b>V-Series Lanyards</b>			
10023933	Diamond Single-Leg Energy-Absorbing Expanyard, 6', 36CL Rebar snaphook	10188103	10190398	V-Series standard single-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36CL large snaphooks	CSA Z259.11-17
10074736	Diamond Single-Leg Energy-Absorbing Lanyard, 5', 36C steel snaphook & 36CL rebar snaphook	10188103	10190398	V-Series standard single-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36CL large snaphooks	CSA Z259.11-17
10053015	Diamond Single-Leg Energy-Absorbing Expanyard, 6', 36CL Rebar snaphook	10188103	10190398	V-Series standard single-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36CL large snaphooks	CSA Z259.11-17
10156541	Diamond LITE Single-Leg Energy-Absorbing Lanyard, 6', AL36CL aluminum snaphook	10188103	10190398	V-Series standard single-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36CL large snaphooks	CSA Z259.11-17
10045938	Diamond Twin-Leg Energy-Absorbing Expanyard, 6', 36CS swivel snaphook & (2) 36CL Rebar snaphooks	10188101	10190400	V-Series standard twin-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36CL large snaphooks	CSA Z259.11-17
10023971	Diamond Twin-Leg Energy-Absorbing Lanyard, 6', 36CS swivel snaphook & (2) 36CL Rebar snaphooks	10188101	10190400	V-Series standard twin-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36CL large snaphooks	CSA Z259.11-17
10156542	Diamond LITE Twin-Leg Energy-Absorbing Lanyard, 6', (2) AL36CL aluminum snaphook	10188101	10190400	V-Series standard twin-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36CL large snaphooks	CSA Z259.11-17



## CSA Weight Chart

The below sizing chart reflects MSA's new weight classes for CSA energy absorbing lanyards that meet Z259.11-17.

User Capacity		Previous CSA EA	New CSA EA		
kg	lb.				
45	100	E4 45–115 kg 100–254 lb.	Lightweight CSA 50–105 kg 100–230 lb.	CSA 68–140 kg 150–310 lb.	
50	110				
55	121				
60	132				
65	143				
70	154				
75	165				
80	176				
85	187				
90	198				
95	209	E6 90–175 kg 200–386 lb.			
100	220				
105	231				
110	243				
115	254				
120	265				
125	276				
130	287				
135	298				
140	309				
145	320	Heavy Worker CSA 140–175 kg 310–386 lb.			
150	331				
155	342				
160	353				
165	364				
170	375				
175	386				
180	397				

Note: This Bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.



**MSA – The Safety Company**  
 1000 Cranberry Woods Drive  
 Cranberry Township, PA 16066 USA  
 Phone 724-776-8600  
[www.MSAafety.com](http://www.MSAafety.com)

**U.S. Customer Service Center**  
 Phone 1-800-MSA-2222  
 Fax 1-800-967-0398

**MSA Canada**  
 Phone 1-800-672-2222  
 Fax 1-800-967-0398

**MSA Mexico**  
 Phone 01 800 672 7222