

MSA and Dynevac® II Rescuers



WE KNOW WHAT'S AT STAKE.

MSA Rescuer

Fast, easy and intuitive fall protection with integral bi-directional retrieval capability. Fast installation and setup; exclusive integral bracket uses existing tripod pin. Can be used as a stand-alone retractable device, as the carrying handle may be used as an anchorage attachment.

Standard features:

- User capacity up to 400 lbs. for personnel
- Stainless steel 3/16" wire rope
- Integral mounting bracket
- Color-coded switch for retrieval mechanism activation
- Ergonomic, stainless steel carrying handle can also be used as anchorage connection point
- Built-in shock absorber
- Robust aluminum housing with thermoplastic bumpers
- Self-locking swivel snaphook with load indicator
- Stow-able, foldable crank handle
- RFID-enabled
- Available in Synthetic Rope
- Meets all applicable OSHA regulations, ANSI Z359.14 and CSA Z259.2.2

Specifications

- **Net weight**
16.3kg (includes bracket)
- **Crank handle material**
Carbon steel with zinc plating
- **Housing material**
Cast aluminum
- **Lifting and lowering gear ratio**
Gear ratio: 5:1
- **Maximum free fall distance**
2 ft. (0.6m)
- **Maximum deceleration distance**
54" (1.4m)
- **Maximum arresting force**
1800 lbs. (8Kn)

			ANSI	CSA
MSA RESCUER	10158178	MSA Rescuer, stainless steel cable, 50 ft. (15m)	■	
	10158180	MSA Rescuer, stainless steel cable, 50 ft. (15m)		■
SYNTHETIC RESCUER	10159755	MSA Rescuer, synthetic rope, 50 ft. (15m)	■	



MSA Rescuer
Part No. 10158178

Dynevac II Self-Retracting Lanyard, Field-Resettable Model

- Emergency retrieval capabilities
- Switch from fall arrest to retrieval modes quickly and simply
- Allows user to reset device in the field from retrieval mode to fall arrest mode
- Simple operation—ready for immediate emergency retrieval
- After fall arrest or retrieval—unit may be reused following competent person inspection
- Provides fall arrest and emergency lifting and lowering for confined space entry
- Available in 95-ft. line length
- Built-in shock absorbing mechanism limits fall arrest forces
- Meets all applicable OSHA regulations, and Z359.14 and CSA as noted in chart below

Specifications

- 4.5-ft. per second locking speed and built-in shock absorber
- 3/16" stainless steel cable
- Forged steel, zinc-plated self-locking swivel snaphook with load indicator
- 3 cam driven, independent braking mechanisms prevent freezing in icy or corrosive conditions
- Average lifting speed of 25-ft. per minute

			ANSI	CSA
DYNEVAC II SELF-RETRACTING LANYARDS	10007783	95' (30m) Self-Retracting Lanyard with Emergency Rescuer, 3/16" diameter stainless steel line		■
	10127295	95' (30m) Self-Retracting Lanyard with Emergency Rescuer, 3/16" diameter stainless steel line	■	



Dynevac II SRL with
Emergency Rescuer
Part No. 10127295

Note: This Bulletin contains only a general description of the products shown. While product uses and performance capabilities are generally described, the products shall not, under any circumstances, be used by untrained or unqualified individuals. The products shall not be used until the product instructions/user manual, which contains detailed information concerning the proper use and care of the products, including any warnings or cautions, have been thoroughly read and understood. Specifications are subject to change without prior notice.

MSA operates in over 40 countries worldwide. To find an MSA office near you, please visit [MSAafety.com/offices](https://www.MSAafety.com/offices).